



ITEM	QTY.	PART #	DESIG.	DESCRIPTION
64	4	25231100	LSW1-LSW4	HATCH LIMIT SWITCH SPDT 6A, 125V 83-853-101
65	1	-----	RECP3	ETHERNET BULKHEAD RECEPTACLE 10/100 BASE T
66	1	-----	[RECP3]	RECEPTACLE COVER
67	1	-----	RDP	OPERATOR INTERFACE 6" MONOCHROME TOUCHSCREEN 24VDC CONTROL POWER
68	1	-----		SUITCASE 13.5" X 12.875" X 6" BLACK, ABS PLASTIC
69	1	25219120	PB1	PUSHBUTTON MOMENTARY, N.O. CONTACT
70	10	25219060	S2-S11	ROTARY SWITCH 2 POSITION 1 N.O. CONTACT
71	75 FT.	25545600		REMOTE CONTROL CABLE 6" #18 AWG OVERALL SHIELDED TWISTED PAIR
72	1	25627100	RECPT 1	BOX MOUNTING RECEPTACLE 10 POLE, #16 AWG CRIMP STYLE SOCKETS
73	1	25627110	RECPT 2	BOX MOUNTING RECEPTACLE 10 POLE, #16 AWG CRIMP STYLE PINS
74	2	25627170	[RECPT 1] [RECPT 2]	PROTECTIVE CAP WITH 6" BEAD CHAIN, OLIVE DRAB

ITEM	QTY.	PART #	DESIG.	DESCRIPTION
75	1	25627150	PLUG 1	CABLE MOUNTING PLUG 10 POLE, #16 AWG CRIMP STYLE PINS
76	1	25627160	PLUG 2	CABLE MOUNTING PLUG 10 POLE, #16 AWG CRIMP STYLE SOCKETS
77	2	25627190	[PLUG 1] [PLUG 2]	CABLE SEALING BACKSHELL 2" MEDIUM DUTY, DIRECT COUPLED, CADMIUM PLATED, OLIVE DRAB
78	2	25627180	[PLUG 1] [PLUG 2]	PROTECTIVE CAP WITH 9" BEAD CHAIN, OLIVE DRAB
79	1	-----	ITS	PANEL CONNECTOR 15 PIN D-SUB TO TERMINAL STRIP FOR RS-485 COMM.
80	AR	25554600	CABLE-2	RS-485 COMMUNICATION CABLE #16 AWG SHIELDED, TWISTED- PAIR, 105°C, PVC
81	1	-----	PR1	POWER RECEPTACLE 50A, 480V, 3 PHASE
82	1	-----	[PR1]	POWER RECEPTACLE COVER
83	1	-----	[PR1]	POWER RECEPTACLE MATING PLUG

THE INFORMATION HEREON IS THE PROPERTY OF SIMPLEX, INC., AND/OR ITS SUBSIDIARIES. WITHOUT WRITTEN PERMISSION ANY COPYING, TRANSMITTAL TO OTHERS AND USE EXCEPT THAT FOR WHICH IT IS LOANED IS PROHIBITED.  
© 2007 SIMPLEX, INC. ALL RIGHTS RESERVED

 ADDED PR1		DRAWN BY : AZM	
		DATE : 3/29/07	
 SPRINGFIELD, ILLINOIS			
SCALE :		APPROVED BY :	
DATE : 3/23/07		DRAWN BY : JPC	
		REVISED :	
RESISTIVE LOAD BANK SATURN 3000 DV 2550KW/3000KW,480V/600V,3ø,60HZ LEGEND 2			
W.O.# 63798-07-43/2		DRAWING NUMBER 47B164481A	