

ITEM	QTY.	PART #	DESIG.	DESCRIPTION
64	4	25231100	LSW1- LSW4	HATCH LIMIT SWITCH SPDT 125V, 6A
65	1	-----	RECPT. 1	ETHERNET BULKHEAD RECEPTACLE 10/100T BASE T
66	1	-----	[RECPT. 1]	ETHERNET BULKHEAD RECEPTACLE COVER 10/100T BASE T
67	1	-----	RDP	OPERATOR INTERFACE 6" MONOCHROME TOUCHSCREEN 24VDC POWER, ETHERNET CAPABLE
68	1	-----		SUITCASE 13.5" X 12.875" X 6" BLACK, ABS PLASTIC
69	1	25219120	PB1	PUSHBUTTON MOMENTARY, N.O. CONTACT
70	15	25219060	S2-S16	ROTARY SWITCH 2 POSITION 1 N.O. CONTACT
71	75 FT.	25545600		REMOTE CONTROL CABLE 6X #18 AWG OVERALL SHIELDED TWISTED PAIR
72	1	25627100	RECPT 1	BOX MOUNTING RECEPTACLE 10 POLE, #16 AWG CRIMP STYLE SOCKETS
73	1	25627110	RECPT 2	BOX MOUNTING RECEPTACLE 10 POLE, #16 AWG CRIMP STYLE PINS

ITEM	QTY.	PART #	DESIG.	DESCRIPTION
74	2	25627170	[RECPT 1] [RECPT 2]	PROTECTIVE CAP WITH 6" BEAD CHAIN, OLIVE DRAB
75	1	25627150	PLUG 1	CABLE MOUNTING PLUG 10 POLE, #16 AWG CRIMP STYLE PINS
76	1	25627160	PLUG 2	CABLE MOUNTING PLUG 10 POLE, #16 AWG CRIMP STYLE SOCKETS
77	2	25627190	[PLUG 1] [PLUG 2]	CABLE SEALING BACKSHELL 2" MEDIUM DUTY, DIRECT COUPLED, CADMIUM PLATED, OLIVE DRAB
78	2	25627180	[PLUG 1] [PLUG 2]	PROTECTIVE CAP WITH 9" BEAD CHAIN, OLIVE DRAB
79	1	-----	CABLE 1	CABLE 15 PIN D-SUB TO WIRES
80	1	-----	ITS	PANEL CONNECTOR 15 PIN D-SUB TO TERMINAL STRIP FOR RS-485 COMM.
81	1	25554600	CABLE 2	RS-485 COMM. CABLE 16 AWG. SHIELDED

THE INFORMATION HEREON IS THE PROPERTY OF SIMPLEX, INC.,
AND/OR ITS SUBSIDIARIES. WITHOUT WRITTEN PERMISSION ANY
COPYING, TRANSMITTAL TO OTHERS AND USE EXCEPT THAT FOR
WHICH IT IS LOANED IS PROHIBITED.
© 2007 SIMPLEX, INC. ALL RIGHTS RESERVED

SIMPLX [®]			SPRINGFIELD, ILLINOIS
SCALE :	APPROVED BY :	DRAWN BY : JPC	
DATE : 3/23/07		REVISED :	
RESISTIVE LOAD BANK 2550KW/3000KW,480V/600V,3ø,60HZ		SATURN 3000 DV LEGEND 2	
W.O.# 63798-07-43/2		DRAWING NUMBER 47B164481	