




FINAL POWERED LOUVER AND
TOP HAT DESIGN TO BE DETERMINED





- NOTES:
1. BOTTOM OF CONTROL COMPARTMENT AVAILABLE FOR CONDUIT ENTRY.
 2. CONSTRUCTION: ALL WELDED FORMED STEEL FRAME, DOORS, PANELS AND SKID.
SKID AND STRUCTURAL MEMBERS 7GA HRS, OUTER SHELL 12GA HRS
AND HINGED DOORS 14GA HRS.
ALL HINGES, EXTERIOR FASTENERS, AND EXTERIOR
HARDWARE ARE STAINLESS STEEL
EXHAUST HOOD IS GALVANIZED SHEET STEEL, RIVETED
 3. SURFACE PREPARATION: ABRASIVE CLEANED OR CHEMICALLY CLEANED AND PHOSPHATIZED
FINISH COLOR: ASA 49 GRAY
PRIMER: TILE CLAD WB EPOXY
(24702501), PART A, B73A200, GRAY PRIMER
(24702502), PART B, B73V200, CATALYST

PAINT: CENTURION POLYURETHANE
(24708500), B65W711, ASA 49 GRAY
(24722500), B65V700, CATALYST
 4. APPROXIMATE SHIPPING WEIGHT: 5,000 LBS. TOTAL UNIT
: 3,800 LBS. LOAD BANK
: 1,200 LBS. TOP HAT



THE INFORMATION HEREON IS THE PROPERTY OF SIMPLEX, INC., AND/OR ITS SUBSIDIARIES. WITHOUT WRITTEN PERMISSION ANY COPYING, TRANSMITTAL TO OTHERS AND USE EXCEPT THAT FOR WHICH IT IS LOANED IS PROHIBITED.

© 2007 SIMPLEX, INC. ALL RIGHTS RESERVED

	REVISED LAYOUT	DRAWN BY :JZ
		DATE : 04/27/07
	REVISED LAYOUT	DRAWN BY :AZM
		DATE : 3/28/07
SIMPLX®		SPRINGFIELD, ILLINOIS
SCALE :	APPROVED BY :	DRAWN BY :JPC
DATE : 3/22/07		REVISED :
RESISTIVE LOAD BANK		SATURN 3000 DY
2550KW/3000KW,480V/600V,3PH.,60HZ		PICTORIAL
W.O. # 63798-07-43/2		DRAWING NUMBER 47BD164460B