



THE INFORMATION HEREON IS THE PROPERTY OF SIMPLEX, INC., AND/OR ITS SUBSIDIARIES. WITHOUT WRITTEN PERMISSION ANY COPYING, TRANSMITTAL TO OTHERS AND USE EXCEPT THAT FOR WHICH IT IS LOANED IS PROHIBITED.
©2007 SIMPLEX, INC. ALL RIGHTS RESERVED.



NOTES:
1. UNIT MUST BE GROUNDED FOR OPERATORS SAFETY.
2. DASHED LINES INDICATE WIRING NOT SUPPLIED BY SIMPLEX.

COLOR CHART

CODE	WIRE GAUGE	INSULATION TEMPERATURE RATING	WIRE COLOR	SIMPLEX PART NUMBER	APPLICATION
AA	16 AWG	105°C	BLACK	25518200	øA, CONTROL - LINE
AB	16 AWG	105°C	RED	25518100	øB
AC	16 AWG	105°C	BLUE	25518300	øC
AD	16 AWG	105°C	WHITE	25518000	CONTROL - NEUTRAL
AE	16 AWG	150°C	BLACK	25515500	LIMIT SWITCH
BM	14 AWG	105°C	GREEN	25525250	GROUND
EE	8 AWG	150°C	BLACK	25533100	øA
EF	8 AWG	150°C	RED	25533200	øB
EG	8 AWG	150°C	BLUE	25533300	øC

NOTES:
1. UNIT MUST BE GROUNDED FOR OPERATORS SAFETY.
2. DASHED LINES INDICATE WIRING NOT SUPPLIED BY SIMPLEX.
3. FOR CONTINUED SAFETY AND MAXIMUM EQUIPMENT PROTECTION, ALWAYS REPLACE ANY FUSE WITH ONE OF EQUAL RATING ONLY.

SIMPLX

SPRINGFIELD, ILLINOIS

SCALE :
DATE : 3/22/07

APPROVED BY :
DRAWN BY : JPC
REVISED :

RESISTIVE LOAD BANK
2550KW/3000KW, 480V/600V, 3ø, 60HZ CONTROL 1

SATURN 3000 DV
2550KW/3000KW, 480V/600V, 3ø, 60HZ CONTROL 1

W.O.#63798-07-43/2

DRAWING NUMBER
47B164461