



- NOTES:
- BOTTOM OF CONTROL COMPARTMENT AVAILABLE FOR CONDUIT ENTRY.
  - CONSTRUCTION: ALL WELDED FORMED STEEL FRAME, DOORS, PANELS AND SKID. SKID AND STRUCTURAL MEMBERS 7GA HRS, OUTER SHELL 12GA HRS AND HINGED DOORS 14GA HRS. ALL HINGES, EXTERIOR FASTENERS, AND EXTERIOR HARDWARE ARE STAINLESS STEEL. EXHAUST HOOD IS GALVANIZED SHEET STEEL, RIVETED.
  - SURFACE PREPARATION: ABRASIVE CLEANED OR CHEMICALLY CLEANED AND PHOSPHATIZED.  
FINISH COLOR: ASA 49 GRAY  
PRIMER: TILE CLAD WB EPOXY (24702501), PART A, B73A200, GRAY PRIMER (24702502), PART B, B73V200, CATALYST  
PAINT: CENTURION POLYURETHANE (24708500), B65W711, ASA 49 GRAY (24722500), B65V700, CATALYST
  - APPROXIMATE SHIPPING WEIGHT: 4,700 LBS. TOTAL UNIT  
: 4,500 LBS. LOAD BANK  
: 200 LBS. TOP HAT

△	REVISED LAYOUT	DRAWN BY :JZ
		DATE : 05/02/07
△	REVISED LAYOUT	DRAWN BY :JZ
		DATE : 04/27/07
△	REVISED LAYOUT	DRAWN BY :AZM
		DATE : 3/28/07
<b>SIMPLX®</b>		SPRINGFIELD, ILLINOIS
SCALE :	APPROVED BY :	DRAWN BY :JPC
DATE : 3/22/07		REVISED :
RESISTIVE LOAD BANK SATURN 3000 DV		
2550KW/3000KW,480V/600V,3PH.,60HZ		PICTORIA
W.O. # 63798-07-43/2		DRAWING NUMBER 47BD164460C

THE INFORMATION HEREON IS THE PROPERTY OF SIMPLEX, INC., AND/OR ITS SUBSIDIARIES. WITHOUT WRITTEN PERMISSION ANY COPYING, TRANSMITTAL TO OTHERS AND USE EXCEPT THAT FOR WHICH IT IS LOANED IS PROHIBITED.

© 2007 SIMPLEX, INC. ALL RIGHTS RESERVED