



SECTION #2
RIGHT SIDE OF
LOAD ENCLOSURE


FRONT OF TRAY #25




FRONT OF TRAY #26




FRONT OF TRAY #27




FRONT OF TRAY #28




FRONT OF TRAY #29





FRONT OF TRAY #30




FRONT OF TRAY #31



FRONT OF TRAY #32



Y-DELTA CONFIGURATION
CONTACTOR EXAMPLE



Y-DELTA CONFIGURATION
CONTACTOR
WIRING EXAMPLE

**** REAR OF ALL TRAYS ARE HOOKED ****
NOTE: TRAYS USED ARE OF THE SATURN 2-C GENERATION;
SEE DRAWING 7BD76946E FOR ASSEMBLY.

CODE	WIRE GAUGE	INSULATION TEMPERATURE RATING	WIRE COLOR	SIMPLEX PART NUMBER	APPLICATION
CE	12 AWG	150°C	BLACK	25531630	600V-ØA, LOAD
CF	12 AWG	150°C	RED	25531620	600V-ØB, LOAD
CG	12 AWG	150°C	BLUE	25531640	600V-ØC, LOAD
CH	12 AWG	150°C	WHITE	25531610	600V, LOAD JUMPER
CN	12 AWG	150°C	YELLOW		600V, SC WIRING
EE	8 AWG	150°C	BLACK	25533100	600V-ØA, LOAD
EF	8 AWG	150°C	RED	25533200	600V-ØB, LOAD
EG	8 AWG	150°C	BLUE	25533300	600V-ØC, LOAD
EH	8 AWG	150°C	WHITE	25533350	600V, LOAD JUMPER
EN	8 AWG	150°C	YELLOW		600V, SC WIRING