




FINAL POWERED LOUVER AND
TOP HAT DESIGN TO BE DETERMINED




REAR VIEW




LEFT SIDE VIEW



FOOTPRINT



FRONT VIEW



RIGHT SIDE VIEW

- NOTES:
1. BOTTOM OF CONTROL COMPARTMENT AVAILABLE FOR CONDUIT ENTRY.
 2. CONSTRUCTION: ALL WELDED FORMED STEEL FRAME, DOORS, PANELS AND SKID. SKID AND STRUCTURAL MEMBERS 7GA HRS, OUTER SHELL 12GA HRS AND HINGED DOORS 14GA HRS. ALL HINGES, EXTERIOR FASTENERS, AND EXTERIOR HARDWARE ARE STAINLESS STEEL. EXHAUST HOOD IS GALVANIZED SHEET STEEL, RIVETED.
 3. SURFACE PREPARATION: ABRASIVE CLEANED OR CHEMICALLY CLEANED AND PHOSPHATIZED
FINISH COLOR: ASA 49 GRAY
PRIMER: (24702501), PART A, B73A200, GRAY PRIMER
(24702502), PART B, B73V200, CATALYST
PAINT: CENTURION POLYURETHANE
(24708500), B65W711, ASA 49 GRAY
(24722500), B65V700, CATALYST
 4. APPROXIMATE SHIPPING WEIGHT: 5,000 LBS. TOTAL UNIT
: 3,800 LBS. LOAD BANK
: 1,200 LBS. TOP HAT

THE INFORMATION HEREON IS THE PROPERTY OF SIMPLEX, INC., AND/OR ITS SUBSIDIARIES. WITHOUT WRITTEN PERMISSION ANY COPYING, TRANSMITTAL TO OTHERS AND USE EXCEPT THAT FOR WHICH IT IS LOANED IS PROHIBITED.

© 2007 SIMPLEX, INC. ALL RIGHTS RESERVED

SIMPLX®			SPRINGFIELD, ILLINOIS
SCALE :	APPROVED BY :	DRAWN BY :JPC	
DATE : 3/22/07		REVISED :	
RESISTIVE LOAD BANK		SATURN 3000 DY	
2550KW/3000KW,480V/600V,3PH.,60HZ		PICTORIA	
W.O. # 63798-07-43/2		DRAWING NUMBER 47BD16446D	