



NOTES:

1. BOTTOM OF CONTROL COMPARTMENT AVAILABLE FOR CONDUIT ENTRY.
 2. CONSTRUCTION: ALL WELDED FORMED STEEL FRAME, DOORS, PANELS AND SKID. SKID AND STRUCTURAL MEMBERS 7GA HRS, OUTER SHELL 12GA HRS AND HINGED DOORS 14GA HRS. ALL HINGES, EXTERIOR FASTENERS, AND EXTERIOR HARDWARE ARE STAINLESS STEEL. EXHAUST HOOD ARE GALVANIZED SHEET STEEL, RIVETED AND PHOSPHATIZED.
 3. SURFACE PREPARATION: ABRASIVE CLEANED OR CHEMICALLY CLEANED AND FINISH COLORED.
- FINISH COLOR: TILE CLAD WB EPOXY
- | | |
|-------------|------------------------------|
| (24702501), | PART A, B73A200, GRAY PRIMER |
| (24722500), | PART B, B73V200, CATALYST |
| (24722500), | ASA 49 GRAY CATALYST |
- PAINT: CENTURION POLYURETHANE
 B65W711, B65V700,
 (24708500), (24722500),
4. APPROXIMATE SHIPPING WEIGHT: 1590 LBS. TOTAL UNIT
 : 1300 LBS LOAD BANK
 : 290 LBS TOP HAT

THE INFORMATION HEREON IS THE PROPERTY OF SIMPLEX, INC., AND/OR ITS SUBSIDIARIES. WITHOUT WRITTEN PERMISSION ANY COPYING, TRANSMITTAL TO OTHERS AND USE EXCEPT THAT FOR WHICH IT IS LOANED IS PROHIBITED.

© 2005 SIMPLEX, INC. ALL RIGHTS RESERVED

DISK S/N: 4473

SIMPLEX		SPRINGFIELD, ILLINOIS	
SCALE:	APPROVED BY :	DRAWN BY :	CJG
DATE : 01-03-06		REVISED:	
RESISTIVE LOAD BANK		NEPTUNE-500 UL	
500KW, 480V, 3Ø, 60Hz		LOAD BANK PICTORIAL	
W.O. # 60723-05-43		DRAWING NUMBER	47BD154283