

# CANNON LOAD BANKS, INC.

PALMETTO, GA. 30268

PHONE 770-463-0504

## MODEL L-69-80

PORTABLE LOAD BANK

The **L-69-80 LOAD BANK** is designed to provide a temporary load for field servicing and testing 480VAC and 208VAC three phase, 60HZ generators and inverters. The L-69-80 load bank is air cooled. A 120VAC outlet is required to operate the fans and relays. The load is 100KW at 480VAC and 80KW at 208VAC.



### MODEL L-69-80 DIMENSIONS

Length.....22"  
Width.....8"  
Height.....21"  
Weight.....60 lbs.

### FEATURES

- Load steps: 12.5, 12.5, 25, 25, 25 KW on three phase 480VAC
- Load steps: 10, 10, 20, 20, 20 KW on three phase 208VAC
- Tests 240VAC three phase, 240VAC single phase and 120VAC single phase
- Plug test pins for connecting test leads
- Receptacle for ten foot cable(included with load bank)
- Meters: 0-600V voltmeter, 0-250A ammeter, 55-65HZ frequency meter
- Power indicator lights
- Thermal protection
- Carrying case

WEBSITE: [WWW.CANNONLOADBANKS.COM](http://WWW.CANNONLOADBANKS.COM)